

HOW TO

REMOVE CARPET

WITHOUT DAMAGING YOUR WOOD FLOORS

Tadas Sadunas | Tadas Wood Flooring Inc.

Removing carpet and all the components that go along with it is not difficult; it just takes some time and is a dirty, dusty job.

It is best to use a dust mask as there will be a lot of dust coming up from beneath the carpet no matter how well you have vacuumed. We also advise you to use sturdy gloves as the tack-strip can give you nasty cuts if you're not careful.

You will also need a sharp retractable knife, a roll of duct tape, a hammer, a pry-bar, a pair of pliers, knee pads and a shop-vac or broom.

TOOLS YOU'LL NEED:

- Dust Mask
- Sturdy Gloves
- Retractable Knife
- Hammer
- Pry Bar
- Pliers
- Roll of Duct Tape
- Knee Pads
- Shop-Vac or Broom

First you will need to cut the carpet into manageable pieces to easily dispose of. We usually cut it into 4ft strips, running the length of the room.

Make sure you lift the carpet so you don't cut into the hardwood floor!

Once the carpet is cut up you can pull it up away from the wall and off the tack-strip.

Then start at one end and roll the strip up. When you have it rolled up, take the roll of duct tape and wrap it around the roll of carpet a couple of times and then put it outside to dispose of. Do the same for the underlay.

We usually leave one section of underlay unrolled till the end so we can put all of the tack-strip in it and roll it up so it won't 'bite' us. There's nothing worse than getting gashed by the hundreds of tiny nails on a

piece of tack-strip as you carry them out. The fun part is now removing all of the tack-strip from around the walls. The easiest way to do this is with a pry bar or a hammer and old chisel or flathead screwdriver.

You'll notice larger nails that have been hammered into the floor every few inches, you want to pry at these spots so as to get the tack-strip out in as big as lengths as possible. Using this leverage makes the task far easier. This is definitely a time to use those gloves. Be careful not to lift up or damage the hardwood flooring as you do this.

Once all the tack-strip is out, break it up into manageable pieces and roll it all up into the strip of underlay you have left over. Duct tape it extra well so it won't slide out.

All that's left now is to remove the hundreds of staples covering the floor as well as any nails around the perimeter left behind from the tack-strip. This is where those pliers and knee pads will come in handy.

Finally, shop-vac or sweep up the floors, double check for any stray staples or nails and enjoy the trip to the dump, thinking about all the money you have just saved!

For video instructions you can visit our YouTube channel and watch a 3 part set of step-by-step videos:

<https://www.youtube.com/user/TadasWoodFlooring>
